

BIG AIR Püre

CEILING FAN



MODEL 26' (8.0 m)

BIG AIR Püre FEATURES

- Very light 5-blade fan with minimum maintenance.
- Innovative safety system designed to prevent propeller detachment.
- Reliable mounting system - completely isolates the fan unit from the facility structure. The system prevents any vibrations or movement from the fan being transferred back to the structure.
- Remarkably silent, even when operating at high velocities.
- Contains a German synthetic oil specially designed for a long lifespan.
- The gear motor technology is a modular system complete with an energy-efficient motor and an adapted gear unit optimally matched to each other. Without couplings and transmission elements, this high-quality system represents the optimum drive solution.

- Effortlessly reversible for year-round use.
- Anti-corrosion anodized aluminum aerodynamic blades.
- Covers an extensive area.

OPTIONAL:

- Easy to use variable remote with a reversible function.
- Drop mount is available.


The most efficient fan on the market with an unmatched airflow per consumed watt

| DIA. | DRIVE | HP (KW) | VOLT | PH | AMP | RPM | HZ | REAL WATT | CFM (M ³ H) | CFM/WATT (M ³ H/WATT) | DB NOISE | BLADES | HANGING WEIGHT | SPEED |
|-------------|-------|---------------|---------|----|---------|-----|-------|-----------|------------------------------------|----------------------------------|----------|--------|-------------------|----------|
| 16' (4.9 M) | DD | 1.5 (1.12 kW) | 230/460 | 3 | 4.6/2.3 | 100 | 50/60 | 962 | 170 223 (289 379 M ³ H) | 177 (301) | 68 | 5-ALUM | 200LBS (90.9 KG) | VARIABLE |
| 20' (6.2 M) | DD | 1.5 (1.12 kW) | 230/460 | 3 | 4.6/2.3 | 88 | 50/60 | 1156 | 289 663 (492 427 M ³ H) | 251 (427) | 64 | 5-ALUM | 220LBS (100.0 KG) | VARIABLE |
| 24' (7.3 M) | DD | 2 (1.50 kW) | 230/460 | 3 | 6.0/3.0 | 71 | 50/60 | 1412 | 448 799 (762 958 M ³ H) | 318 (541) | 61 | 5-ALUM | 245LBS (111.4 KG) | VARIABLE |
| 26' (8.0 M) | DD | 2 (1.50 kW) | 230/460 | 3 | 6.0/3.0 | 62 | 50/60 | 1444 | 461 815 (785 137 M ³ H) | 320 (544) | 61 | 5-ALUM | 255LBS (115.9 KG) | VARIABLE |



OPTIMIZED BLADE DESIGN

The more aggressive design of the wider blades optimizes aerodynamics, the downward airflow, and reduces the noise level to the minimum. The blades are also thicker to withstand vibrations better.



WHY THE "BLUE MACHETE"

The "Blue Machete" whips the air at the ends of the blades and thus increases its speed. It also widens the air intake area for better circulation. The "Blue Machete" increases the performance by 5%.

For more information

skov-secco.com

info@skov-secco.com

